

ProCAM™ DVD

Color Mini Camera Inspection System with DVD Player/Recorder

The ProCam DVD® by UEMSI, is an extremely compact and lightweight mini camera system you can't live without. Having the same high quality standards and durability you have come to expect from UEMSI, the ProCam DVD system is the new standard of the industry. It incorporates the latest technology, which includes a 10.4" color LCD monitor and a DVD player / recorder in a heavy-duty case, with a total weight of only 23 pounds. The ProCam DVD system not only operates on both 110 VAC and 12 VDC, but also has a rechargeable battery pack option available. The system is designed for inspecting sewer pipelines, HVAC ducts, chimneys and other enclosed cavities.

Standard with the ProCam DVD system is UEMSI's proven multi-conductor video push cable. It is the strongest in the industry enabling the user to push long runs, yet flexible to handle tight corners in small pipe. The cable also includes a water-blocking gel inside to prevent water infiltration, if it were to become damaged.

ProCAM DVD: It is equipped with our interchangeable, 1.4" OD x 2" L, CM-1 color camera head, as well as the standard features listed below.

ProCAM DVD ULTRA: It is equipped with everything the ProCam DVD has, plus the Data Display I package.

UPGRADE OPTIONS:

PRO EYE SELF-LEVELING COLOR CAMERA HEAD: The Pro Eye self-leveling camera head automatically keeps the picture upright, and is available on both the ProCam DVD and DVD Ultra. It is 1.67" OD x 2.375" L and has 21 white LEDs.

CH-3 COLOR CAMERA HEAD: The CH-3 camera head is used for televising larger pipelines, and is available on both the ProCam DVD and DVD Ultra. It is 2.25" OD x 3" L and has 12 high output incandescent lamps.

DATA DISPLAY I PACKAGE: This package includes a mini-keyboard to add on-screen text, and an on-screen digital footage counter. Footage is accurately measured using a mechanical footage counter instead of being calculated by reel revolution. This package is standard on the ProCam DVD Ultra.



The ProCam DVD Ultra system is shown with standard features including reel w/ 200' of video push cable, CM-1 color camera head and Data Display I package w/ keyboard.

STANDARD FEATURES

- 10.4" color LCD monitor
- DVD player / recorder
- Hand held microphone
- Variable light intensity
- Snap-on sun shield
- Video and audio output RCA connections
- Power control unit only weighs 17 lbs.
- 200' of video push cable with water-blocking gel
- Camera mounted on 8" flexible spring for easy bend negotiation
- Capable of inspecting a minimum of 2" straight pipe
- Cable reel constructed of lightweight, heavy-duty steel tubing
- Maintenance-free slip ring
- Lightweight and durable aluminum camera housing
- 110 VAC or 12 VDC operation
- 4"- 6" Brush skid

UEMSI

PIPELINE CLEANING & TELEVISIONS EQUIPMENT

Corporate Office: 800.688.0766

Website: www.uemsi.com Email: info@uemsi.com

SPECIFICATIONS

REEL ASSEMBLY

- Durable steel construction
- Maintenance-free slip ring
- Rugged wheels for easy mobility
- Fiberglass rod imbedded in video cable for rigidity
- 8" flexible spring for easy bend negotiation
- Reel dimensions: 34" H x 14" W x 30" L
- Reel weight w/ 200' of cable: 49 lbs.
- Hand brake prevents cable reel from turning during transport

CM-1 COLOR CAMERA HEAD

- Video output: 1.0 V p-p NTSC standard, 75 ohm
- Imaging device: 2 lux solid state
- 2:1 interlace scanning
- Scan frequency: 15.734 KHz; 59.9 Hz
- 300,000 pixels
- 460 lines (h) resolution
- 100° lens, 2.5 mm, f 1.8
- Power: 12 VDC
- O-Ring sealed aluminum housing
- Equipped with 15 white LEDs
- Variable light output
- Lighthead housing: high strength, clear polycarbonate
- Camera dimensions: 1.4" OD x 2" L
- Camera weight: 3 oz.

POWER CONTROL UNIT

- Rugged, lightweight, easy-to-carry briefcase-style power control unit case
- Hinged lid with built-in storage compartment
- Power indicator LED
- Complete monitor and camera controls with variable light intensity
- 10.4" color LCD monitor
- DVD player / recorder
- Snap-on sun shield
- Video and audio output connections
- Light head power supply: 0-12 VDC
- Case dimensions: 5.375" H x 14.25" W x 16.375" L
- Weight: 17 lbs.

OPTIONS



PRO EYE SELF LEVELING CAMERA



6"-15" CENTERING SKIDS
ROLLER SKID (LEFT), BRUSH
SKID (MIDDLE), ALUMINUM
SKID (RIGHT)



CH-3 COLOR CAMERA HEAD



TRACKER® & TRACKER® II
LOCATING RECEIVERS



TRACKER® IN-LINE
TRANSMITTER



TRACKER® III & TRACKER® IV
LOCATING RECEIVERS



MINI REEL

OPTIONS NOT PICTURED

- 250' AND 300' CABLE LENGTHS
- DATA DISPLAY I PACKAGE
- RECHARGEABLE BATTERY PACK
- USB Video Capture